

## Single Combination

| INDOOR                |         |               |            | DM07RH NSJ            | DC09RH NSJ            | DC12RH NSJ            |
|-----------------------|---------|---------------|------------|-----------------------|-----------------------|-----------------------|
| Capacity              | Cooling | Rated         | W          | 2,100                 | 2,500                 | 3,500                 |
|                       | Heating | Rated         | W          | 2,300                 | 3,200                 | 4,000                 |
| Sound Pressure        | Cooling | S / L / M / H | dB(A)      | 19 / 27 / 31 / 36     | 19 / 27 / 32 / 36     | 19 / 29 / 34 / 38     |
|                       | Heating | L / M / H     | dB(A)      | 27 / 31 / 36          | 27 / 32 / 36          | 29 / 34 / 39          |
| Sound Power           | Cooling | Power         | dB(A)      | 56                    | 56                    | 56                    |
| Air Flow Rate         | Cooling | S / L / M / H | m³/min     | 3.0 / 5.0 / 6.1 / 7.4 | 3.5 / 5.0 / 6.4 / 7.7 | 3.5 / 5.3 / 6.7 / 8.1 |
|                       |         | Max. (Power)  | m³/min     | 10.1                  | 10.1                  | 10.1                  |
|                       | Heating | L / M / H     | m³/min     | 5.0 / 6.1 / 7.4       | 5.0 / 6.4 / 7.7       | 5.3 / 6.7 / 8.1       |
| Dehumidification Rate |         |               | l/h        | 0.9                   | 1.1                   | 1.2                   |
| Power Supply          |         |               | Ø / V / Hz | 1 / 220-240 / 50      | 1 / 220-240 / 50      | 1 / 220-240 / 50      |
| Power Supply Cable    |         |               | N x mm²    | 4C x 0.75             | 4C x 0.75             | 4C x 0.75             |
| Dimension             |         |               | mm         | 837 x 308 x 189       | 837 x 308 x 189       | 837 x 308 x 189       |
| Net Weight            |         |               | kg         | 8.3                   | 9.1                   | 9.1                   |

| INDOOR                |         |               |            | DC18RH NSK               | DC24RH NSK               |
|-----------------------|---------|---------------|------------|--------------------------|--------------------------|
| Capacity              | Cooling | Rated         | W          | 5,000                    | 6,600                    |
|                       | Heating | Rated         | W          | 5,800                    | 7,500                    |
| Sound Pressure        | Cooling | S / L / M / H | dB(A)      | 31 / 34 / 42 / 47        | 31 / 34 / 42 / 47        |
|                       | Heating | L / M / H     | dB(A)      | 34 / 42 / 47             | 34 / 42 / 47             |
| Sound Power           | Cooling | Power         | dB(A)      | 60                       | 64                       |
| Air Flow Rate         | Cooling | S / L / M / H | m³/min     | 8.0 / 10.5 / 13.1 / 15.5 | 8.0 / 10.5 / 13.1 / 16.1 |
|                       |         | Max. (Power)  | m³/min     | 16.8                     | 18.3                     |
|                       | Heating | L / M / H     | m³/min     | 10.5 / 13.1 / 15.5       | 10.5 / 13.1 / 16.1       |
| Dehumidification Rate |         |               | l/h        | 1.9                      | 2.6                      |
| Power Supply          |         |               | Ø / V / Hz | 1 / 220-240 / 50         | 1 / 220-240 / 50         |
| Power Supply Cable    |         |               | N x mm²    | 4C x 0.75                | 4C x 0.75                |
| Dimension             |         |               | mm         | 998 x 345 x 210          | 998 x 345 x 210          |
| Net Weight            |         |               | kg         | 11.9                     | 12.7                     |